

# Contents

1	Introduction	1
1.1	The <i>fib</i> Model Code for Concrete Structures 2010	1
1.2	Bond and anchorage: General	1
1.3	Influence of bond on structural performance	2
1.4	The need for a comprehensive review	3
1.5	Bond of embedded reinforcement in the <i>fib</i> MC2010	4
1.6	Scope of review	4
2	Review	5
2.1	General trends	5
2.2	Expressions for strength of laps and anchorages	6
3	Derivation of semi-empirical expressions for bond and anchorage	10
3.1	Bond and anchorage of straight bars in tension	10
3.1.1	Introduction	10
3.1.2	Calibration and validation of model	11
3.1.3	Comparison with other semi-empirical expressions	18
3.1.4	Derivation of characteristic bond strength for design	25
3.1.5	Confinement from cover and secondary reinforcement	28
3.1.6	Comparison with data fit of existing design codes	31
3.2	Lapped joints of bars in compression	34
3.2.1	Introduction	34
3.2.2	Calibration and validation	36
3.2.3	Comparison with other semi-empirical expressions	38
3.2.4	Derivation of characteristic values	39
3.2.5	Comparison with data fit of existing design codes	41
3.3	Contribution of hooks and bends	43
3.3.1	Introduction	43
3.3.2	Calibration and validation of model	46
3.3.3	Derivation of characteristic strength for design	48
3.3.4	Comparison with fit of EC2 rules	49
3.4	Effect of transverse pressure	50
3.4.1	Transverse compression: Calibration and validation of model	50
3.4.2	Comparison with other semi-empirical expressions	55
3.4.3	Derivation of characteristic values	55
3.4.4	Comparison with existing design codes	56
3.4.5	Transverse tension	57
3.5	Further validations	58
3.5.1	ASTM A1035 high strength bars: Seleim et al (2009)	58
3.5.2	Hooked and bent bars subjected to transverse compression: Amin's tests	60
3.5.3	End supports to simply supported beams without transverse pressure: Magnusson's tests	61
3.6	Rib geometry	63
3.7	Summary	65
4	Additional detailing issues	66
4.1	Introduction	66
4.2	Minimum covers and spacing	67
4.3	Minimum confining reinforcement	68
4.4	Continuity of reinforcement in lap joints	73
4.5	Location of lapped joints	78
4.6	Transverse pressure from loads and support reactions	81
4.7	Interaction of bond and shear requirements	83

4.8	Bundled bars	84
4.9	Bars in layers	87
4.10	End cover to compression bars	88
4.11	Headed bars	89
4.12	Casting location	92
4.13	Lapped bars of different diameter	93
4.14	Beam-column connections	93
4.15	Minimum anchorage lengths	93
4.16	Minimum lap lengths	93
5	Comparison with existing code provisions	94
5.1	Introduction	94
5.2	Tension lapped joints	94
5.3	Compression lapped joints	98
5.4	Anchorage of bottom reinforcement at end supports, straight bar	99
5.5	Anchorage of bottom reinforcement at end supports, bent bar	102
5.6	Internal support, continuous beam	104
5.7	Beam anchorage, internal column	108
5.8	Summary	109
6	Additional items	110
6.1	Introduction	110
6.2	Welded wire fabric	110
6.3	Slipform construction	110
6.4	Bentonite walling	110
6.5	Post-installed reinforcement	110
6.6	ECE (electrochemical extraction of chlorides)	111
6.7	Fusion bonded epoxy-coated reinforcement	111
6.8	Cryogenic conditions	112
6.9	Elevated temperatures	112
6.10	Degradation from corrosion	113
6.11	Degradation from ASR	113
6.12	Degradation from frost	113
6.13	Degradation from fire	114
7	Derivation of simplified (Level 1) provisions	115
7.1	Introduction	115
7.2	Tension laps	116
7.3	Compression laps	117
7.4	Anchorage of straight bars, no transverse compression	117
7.5	Anchorage of hooked and bent bars, no transverse compression	117
7.6	Anchorage of straight bars subjected to transverse compression	117
7.7	Anchorage of hooked/bent bars subjected to transverse compression	118
8	Relationship with local bond-slip model	119
9	Influence of bond on performance under service loading	120
Appendix A:	Ultimate bond strength of lapped joints and anchorages of straight ribbed bars	121
A.1	General derivation of semi-empirical model for bond strength	121
Appendix B:	Outline of MC90 and EC2 provisions for design of tension anchorages and lapped joints	125
B.1	Summary of MC90 rules	125

B.2	Summary of EC2 rules	126
Appendix C:	Example calculations	128
C.1	Example 1: Beam	128
C.1.1	Data input	128
C.1.2	Beam design and detailing	129
C.1.3	Calculation of the anchorage length C - $l_{b,C}$	131
C.1.4	Calculation of the anchorage length A - $l_{b,A}$	134
C.1.5	Calculation of the anchorage length at the external supports- $l_{b,Es}$	136
C.1.6	Calculation of the lap length of bars in compression at the internal support - $l_{b,Is}$	139
C.2	Example 2: Column	142
C.2.1	Data input and column details	142
C.2.2	Calculation of the lap length	142
C.3	Example 3: Flat slab	144
C.3.1	Data input and flat slab details	144
C.3.2	Calculation of the anchorage length	146
C.4	Example 4: Lap length in a column of a seismic resistant frame	147
C.4.1	Data input and column details	147
C.4.2	Design of the tension lap length within the critical region	149
C.4.3	Design of the lap length outside the critical region	151
C.5	Example 5: External beam column connection	151
C.5.1	Data input and geometry details	151
C.5.2	Calculation of the anchorage length of the upper bars	152
C.5.3	Calculation of the anchorage length of the lower bars	154
References		156