

Contents

| | | |
|----------|--|-----------|
| 1 | Introduction | 1 |
| 2 | Scope | 1 |
| 3 | Type of defects | 3 |
| 3.1 | Geometrical deviations | 3 |
| | (3.1.1 Prior considerations – 3.1.2 Recommended references – 3.1.3 Practical application of tolerance system) | |
| 3.2 | Surface texture – Aesthetics | 5 |
| | (3.2.1 Evenness of surfaces – 3.2.2 Colour and darkness variation – 3.2.3 Cracking of surfaces) | |
| 3.3 | Deflection and camber | 12 |
| 3.4 | Cracks | 13 |
| | (3.4.1 Introduction – 3.4.2 Thermal cracks – 3.4.3 Plastic settlement and autogenous shrinkage cracks – 3.4.4 Drying shrinkage cracks – 3.4.5 Mechanical cracks) | |
| 3.5 | Spalling, splitting and bursting | 15 |
| | (3.5.1 Introduction – 3.5.2 Splitting cracks – 3.5.3 Bursting cracks – 3.5.4 Spalling cracks) | |
| 3.6 | Accidental damage | 16 |
| 4 | General aspects classification | 17 |
| 4.1 | Level of safety required | 17 |
| 4.2 | Durability | 17 |
| 4.3 | Aesthetic issues | 18 |
| 5 | Specific cases | 19 |
| 5.1 | Columns and beams | 20 |
| 5.2 | Panels | 35 |
| | (5.2.1 Load bearing panels – 5.2.2 Non load bearing panels) | |
| 5.3 | Hollow core slabs | 39 |
| 5.4 | Double tee units | 47 |
| 5.5 | Solid planks | 52 |
| 5.6 | Beams and blocks | 54 |
| 6 | Bibliography | 61 |
| | Annex | 63 |
| A.1 | Calculating strength capacity reduction due to a defect | 63 |
| A.2 | Maximum allowable strength loss | 65 |
| A.3 | Examples | 66 |